

# Appendix: AP<sup>®</sup> Physics 1 Equation Tables

## ADVANCED PLACEMENT PHYSICS 1 TABLE OF INFORMATION (2024)

CONSTANTS AND CONVERSION FACTORS	
Universal gravitational constant, $G = 6.67 \times 10^{-11} \text{ m}^3 / (\text{kg} \cdot \text{s}^2) = 6.67 \times 10^{-11} \text{ N} \cdot \text{m}^2 / \text{kg}^2$ 1 atmosphere of pressure, $1 \text{ atm} = 1.0 \times 10^5 \text{ N/m}^2 = 1.0 \times 10^5 \text{ Pa}$	Acceleration due to g ravity at Earth's surface, $g = 9.8 \text{ m/s}^2$ Magnitude of the gravitational field strength at the Earth's surface, $g = 9.8 \text{ N/kg}$



PREFIXES		
Factor	Prefix	Symbol
$10^{12}$	tera	T
$10^9$	giga	G
$10^6$	mega	M
$10^3$	kilo	k
$10^{-2}$	centi	c
$10^{-3}$	milli	m
$10^{-6}$	micro	$\mu$
$10^{-9}$	nano	n
$10^{-12}$	pico	p

UNIT SYMBOLS	hertz,	Hz	newton,	N
	joule,	J	pascal,	Pa
	kilogram,	kg	second,	s
	meter,	m	watt,	W

VALUES OF TRIGONOMETRIC FUNCTIONS FOR COMMON ANGLES							
$\theta$	$0^\circ$	$30^\circ$	$37^\circ$	$45^\circ$	$53^\circ$	$60^\circ$	$90^\circ$
$\sin \theta$	0	1/2	3/5	$\sqrt{2}/2$	4/5	$\sqrt{3}/2$	1
$\cos \theta$	1	$\sqrt{3}/2$	4/5	$\sqrt{2}/2$	3/5	1/2	0
$\tan \theta$	0	$\sqrt{3}/3$	3/4	1	4/3	$\sqrt{3}$	$\infty$

The following conventions are used in this exam.

- The frame of reference of any problem is assumed to be inertial unless otherwise stated.
- Air resistance is assumed to be negligible unless otherwise stated.
- Springs and strings are assumed to be ideal unless otherwise stated.
- Fluids are assumed to be ideal, and pipes are assumed to be completely filled by fluid, unless otherwise stated.

GEOMETRY AND TRIGONOMETRY			
Rectangle $A = bh$	Rectangular Solid $V = \ell wh$		Right Triangle $a^2 + b^2 = c^2$
Triangle $A = \frac{1}{2}bh$	Cylinder $V = \pi r^2 \ell$ $S = 2\pi r \ell + 2\pi r^2$		$\sin \theta = \frac{a}{c}$ $\cos \theta = \frac{b}{c}$ $\tan \theta = \frac{a}{b}$
Circle $A = \pi r^2$ $C = 2\pi r$ $s = r\theta$	Sphere $V = \frac{4}{3}\pi r^3$ $S = 4\pi r^2$		
		$A = \text{area}$ $b = \text{base}$ $C = \text{circumference}$ $h = \text{height}$ $\ell = \text{length}$ $r = \text{radius}$ $s = \text{arc length}$ $S = \text{surface area}$ $V = \text{volume}$ $w = \text{width}$ $\theta = \text{angle}$	

MECHANICS AND FLUIDS		
$v_x = v_{x0} + a_x t$	$a = \text{acceleration}$	$\omega = \omega_o + at$ $a = \text{acceleration}$
$x = x_o + v_{x0}t + \frac{1}{2}a_x t^2$	$d = \text{distance}$	$\theta = \theta_o + \omega_o t + \frac{1}{2}\alpha t^2$ $A = \text{amplitude or area}$
$v_x^2 = v_{x0}^2 + 2a_x(x - x_o)$	$E = \text{energy}$	$\omega^2 = \omega_o^2 + 2\alpha(\theta - \theta_o)$ $d = \text{distance}$
$\vec{x}_{cm} = \frac{\sum m_i \vec{x}_i}{\sum m_i}$	$F = \text{force}$	$v = r\omega$ $f = \text{frequency}$
$\vec{a}_{sys} = \frac{\sum \vec{F}}{m_{sys}}$	$J = \text{impulse}$	$a_r = r\alpha$ $F = \text{force}$
$ F_g  = G \frac{m_1 m_2}{r^2}$	$k = \text{spring constant}$	$\tau = r_{\perp} F = rF \sin \theta$ $h = \text{height}$
$ \vec{F}_f  \leq  \mu \vec{F}_n $	$K = \text{kinetic energy}$	$I = \sum m_i r_i^2$ $I = \text{rotational inertia}$
$\vec{F}_s = -k\Delta\vec{x}$	$m = \text{mass}$	$I' = I_{cm} + Md^2$ $k = \text{spring constant}$
$a_c = \frac{v^2}{r}$	$p = \text{momentum}$	$\alpha_{sys} = \frac{\sum \tau}{I_{sys}} = \frac{\tau_{net}}{I_{sys}}$ $K = \text{kinetic energy}$
$K = \frac{1}{2}mv^2$	$P = \text{power}$	$K = \frac{1}{2}I\omega^2$ $\ell = \text{length}$
$W = F_{\parallel}d = Fd \cos \theta$	$r = \text{radius, distance, or position}$	$W = \tau\Delta\theta$ $L = \text{angular momentum}$
$\Delta K = \sum W_i = \sum F_{\parallel,i} d_i$	$t = \text{time}$	$L = I\omega = rmv \sin \theta$ $m = \text{mass}$
$U_G = -\frac{Gm_1 m_2}{r}$	$U = \text{potential energy}$	$\Delta L = \tau\Delta t$ $M = \text{mass}$
$\Delta U_g = mg\Delta y$	$v = \text{velocity or speed}$	$\Delta x_{cm} = r\Delta\theta$ $P = \text{pressure}$
$P_{avg} = \frac{W}{\Delta t} = \frac{\Delta E}{\Delta t}$	$W = \text{work}$	$T = \frac{1}{f}$ $r = \text{radius, distance, or position}$
$P_{inst} = F_{\parallel}v = Fv \cos \theta$	$x = \text{position}$	$T_s = 2\pi\sqrt{\frac{m}{k}}$ $t = \text{time}$
$\vec{p} = m\vec{v}$	$y = \text{height}$	$T_p = 2\pi\sqrt{\frac{\ell}{g}}$ $T = \text{period}$
$\vec{F}_{net} = \frac{\Delta\vec{p}}{\Delta t} = m \frac{\Delta\vec{v}}{\Delta t} = m\vec{a}$	$\theta = \text{angle}$	$x = A \cos(2\pi ft)$ $v = \text{velocity or speed}$
$\vec{J} = \vec{F}_{avg} \Delta t = \Delta\vec{p}$	$\mu = \text{coefficient of friction}$	$x = A \sin(2\pi ft)$ $V = \text{volume}$
$\vec{v}_{cm} = \frac{\sum \vec{p}_i}{\sum m_i} = \frac{\sum m_i \vec{v}_i}{\sum m_i}$		$W = \text{work}$
		$x = \text{position}$
		$y = \text{vertical position}$
		$\alpha = \text{angular acceleration}$
		$\theta = \text{angle}$
		$\rho = \text{density}$
		$\tau = \text{torque}$
		$\omega = \text{angular speed}$
		$P = P_o + \rho gh$
		$P_{gauge} = \rho gh$
		$F_b = \rho Vg$
		$A_1 v_1 = A_2 v_2$
		$P_1 + \rho gy_1 + \frac{1}{2}\rho v_1^2 = P_2 + \rho gy_2 + \frac{1}{2}\rho v_2^2$